Product Information



BRETFORD MANUFACTURING, INC. 11000 Seymour Avenue Franklin Park, Illinois 60131 USA

Phone: 847.678.2545 Toll-Free Phone: 800.521.9614 Fax: 847.678.0852

Toll-Free Fax: 800.343.1779 www.bretford.com

> 3541-GM_, 3542-GM_, 3501-GM_, 3558-GM_ and 3562-GM_ Connections Adjustable Work Centers with casters for Primary Grade Users



60"W x 24"D x 20-25"H

72"W x 24"D x 20-25"H

FEATURES & BENEFITS

- Attractive Grey laminated tabletop trimmed with a choice of four trim colors
- Large worksurface neatly holds two computers side-by-side
- 14-gauge sturdy steel base with a unique "Y" shape design
- Adjustable in one inch increments from 20"-25" high for primary grades
- Modesty panel offers additional leg room and easy accessibility to the power switch
- Cord management bin and grommet holes hide and organize electrical cords
- One 1½" x 4" grommet hole centered on 36" and 42"W tables
- Two $1\frac{1}{2}$ " x 4" grommet holes on the 48", 60" and 72"W tables
- Accessory Low Rise shelf holds monitor or reference materials
- Comes with 4" casters
- Optional UL-listed 4 outlet electrical unit with single switch power control

DIMENSIONS

- 3541-GM_: 36"W x 24"D x 20-25"H
 3501-GM_: 42"W x 24"D x 20-25"H
 3562-GM_:
- 3542-GM_: 48"W x 24"D x 20-25"H

COLOR/FINISH

- Base: Grey powder paint with grey tube caps
- Tabletops: Grey laminate with choice of four trim colors: Quartz (GMQ), Cardinal (GMC), Topaz (GMT) and Polo (GML)
- Endcaps: Available in choice of Quartz (GMQ), Cardinal (GMC), Topaz (GMT) and Polo (GML)

Product Specifications

Phone: 847.678.2545

Fax: 847.678.0852

3541-GM_, 3542-GM_, 3501-GM_, 3558-GM_ & 3562-GM_ CONNECTIONS ADJUSTABLE HEIGHT TABLES WITH CASTERS

Select one of these two tables when you need a mobile table that lets you take your computer equipment from room to room with ease. The 24" depth lets you maneuver quickly through doorways. Tables feature grommet holes and hinged cord management bins for cords and wires along with integrated modesty panels.

STANDARD EQUIPMENT

Table top (1)

Right leg assembly (1)

Left leg assembly (1)

Modesty panel (1)

Cord management bin (1)

4" locking casters (2)

4" non-locking casters (2)

ACCESSORIES

3530 36"W Low Rise Shelf 3531 48"W Low Rise Shelf 3557-GM Flat Connecting Bracket 3573-GM Connections Bridge Pack 35CPU2-GM CPU Holder w/ Casters

CFPS Surge Protected Electrical Unit


UCSKD-GM Keyboard Drawer UCSSD-GM Supply Drawer

WEIGHT AND FREIGHT CLASS

3541-GM_: 71 pounds, Freight class 70 UPS. 3542-GM_: 80 pounds, Freight class 70. 3501-GM_: 79 pounds, Freight class 70. 3558-GM_: 109 pounds, Freight class 70. 3562-GM_: 107 pounds, Freight class 70.

CONSTRUCTION

Laminate table top made with 1" thick 45 lb. density particle board and $^{1}\!\!/^{u}$ Vinyl "T" molding. Top upright of leg assembly constructed from 1 $^{1}\!\!/^{u}$ x 2" 14 gauge steel tube. Bottom upright and bottom bar of base constructed from 1" x 1 $^{3}\!\!/^{u}$ 14 gauge steel tube. The "Y" shape of leg constructed from 1" square 18-gauge steel tube welded to 14-gauge steel top support. Table base to include 18-gauge steel modesty panel. Cord management bin shall be constructed from 20-gauge steel.



SUGGESTED SPECIFICATIONS

3541-GM_, 3542-GM_, 3501-GM_, 3558-GM_ and 3562-GM_ is height adjustable from 20-25" in 1" increments. Width is 36"W, 42"W, 48"W, 60"W or 72"W depending on the model. Table top is constructed from 1" thick laminate particle board, 45 pound density. The cord management bin is constructed from 20-gauge steel and measures 4"H x 53/8"D. It runs the width of the table, allowing space for optional shelves to be attached. One side is attached to the back of the modesty panel with hinges, and the other side closes with the choice of a thumb screw or theft proof screw (included) which attach to the bottom of the work surface. On the 3541 and 3501, there is one grommet hole measuring 1½" x 4" centered on the work surface. The 3542, 3558 and 3562 have two grommet holes located 24" apart. The modesty panel is made from 18-gauge steel. Top upright of leg assembly constructed from 11/4" x 2" 14 gauge steel tube. Bottom upright and bottom bar of base constructed from 1" x 13/4" 14-gauge steel tube. The "Y" shape of leg constructed from 1' square 18-gauge steel tube welded to 14-gauge steel top support. All models are finished in Grey powder paint, and ship ready to assemble in one carton pack.

Toll-Free Fax: 800.343.1779

Toll-Free Phone: 800.521.9614